



243 Jubug-ri, Yangji-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do 449-822, Korea
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

EMC TEST REPORT

Dates of Tests: May 16 - 26, 2019
 Test Report S/N: LR500121905AE
 Test Site : LTA Co., Ltd.

Model No.

DC-T4533HRX

APPLICANT

IDIS CO., LTD.

Equipment Name : Network Camera
 Manufacturer : IDIS CO., LTD.
 Model name : DC-T4533HRX
 Additional Model name : NC-T4533HRX, DC-T3345HRX
 Test Device Serial No.: Identification
 Directive : Electromagnetic Compatibility Directive 2014/30/EU
 Rule Part(s) : EN 55032:2015
 EN 50130-4:2011/A1:2014
 EN 61000-3-2:2014
 EN 61000-3-3:2013
 Data of reissue : May 29, 2019

This test report is issued under the authority of:

The test was supervised by:

Young Kyu Shin, Technical Manager

Joo Hyung Cho, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Revision	Date of issue	Test report No.	Description
0	29.05.2019	LR500121905AE	Initial

TABLE OF CONTENTS

1. General information's	4
2. Information's about test item	5
3. Test Report	8
3.1 Summary of tests	8
3.2 EMISSION	9
3.2.1 Conducted emissions	9
3.2.2 Radiated Emission	15
3.2.3 Harmonic Current (AC power input port)	23
3.2.4 Voltage Variation and Flicking (AC power input port).....	25
3.3 IMMUNITY	28
3.3.1 Electrostatic Discharge	28
3.3.2 RF Electromagnetic Field	32
3.3.3 Electrical fast transients	34
3.3.4 Surge	35
3.3.5 Conducted disturbances, induced by radio-frequency fields	37
3.3.6 Mains supply voltage dips, short interruptions	39
3.3.7 Mains supply voltage variations	40
APPENDIX A TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS.....	41
APPENDIX B PERFORMANCE CRITERIA	45
APPENDIX C PHOTOGRAPHS	48

1. General information's

1-1 Test Performed

Company name : **LTA Co., Ltd.**
 Address : 243, Jubug-ri, Yangji-Myeon, Yongin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2019-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2021-04-11	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
		T-2416,	2020-09-10	
		R-4483(10 m),	2020-10-15	
		G-10847	2022-06-13	
IC	CANADA	5799A-2	2019-06-15	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information's about test item

2-1 Client/ Manufacturer

Company name : IDIS CO., LTD.
 Address : 8-10, TECHNO 3-RO, YUSEONG-GU, DAEJEON, KOREA
 Telephone / Facsimile : +82-31-723-5205 / +82-31-723-5108

Factory 1

Company name : IDIS CO., LTD.
 Address : 8-10, TECHNO 3-RO, YUSEONG-GU, DAEJEON, KOREA

2-2 Equipment Under Test (EUT)

Class : A
 Equipment Name : Network Camera
 Model name : DC-T4533HRX
 Additional Model Name : NC-T4533HRX, DC-T3345HRX
 Additional Models are identical to DC-T4533HRX except for Model Name, marketing purpose.
 Serial number : Identification
 Date of receipt : May 10, 2019
 EUT condition : Pre-production, not damaged
 Interface ports : DC IN, LAN, ALARM IN, GND, ALARM OUT, AUDIO IN, AUDIO OUT, Micro SD Card
 Power rating : DC 12 V
 Modulator : -
 Crystal/Oscillator(s) : -
 Firmware version : XXXX

2-3 Modification

-NONE

2-4 Model Specification

-NONE

2-5 Test conditions

Temp. / Humid. / Pressure : +(22 - 25) °C / (33 - 43) % R.H. / (100) kPa
 Tested Model : DC-T4533HRX
 Test mode : REC mode (Adapter), REC mode (POE)
 Power supply : AC 230 V, 50 Hz

2-5 EUT

Equipment	Model No.	Serial No.	Manufacturer
Network Camera	DC-T4533HRX	N/A	IDIS CO., LTD.

2-6 Accessory / REC mode (Adapter)

Equipment	Model No.	Serial No.	Manufacturer
Notebook	N16Q2	NXGRYSJ00 17300B5F77600	Acer
Mobile phone	SM-J700K	N/A	SAMSUNG
ALARM #1	N/A	N/A	N/A
ALARM #2	SPL-0030	N/A	SECOM
Micro SD Card	N/A	N/A	Sandisk
Adapter	F12L2-120100SPAK	N/A	SHENZHEN FRECOM ELECTRONICS CO.,LTD.
Speaker	WS-30T	N/A	InterM

/ REC mode (POE)

Equipment	Model No.	Serial No.	Manufacturer
Notebook	N16Q2	NXGRYSJ00 17300B5F77600	Acer
Mobile phone	SM-J700K	N/A	SAMSUNG
ALARM #1	N/A	N/A	N/A
ALARM #2	SPL-0030	N/A	SECOM
Micro SD Card	N/A	N/A	Sandisk
PoE Injector	POE16R-1AFG	N/A	PHIHONG
Speaker	WS-30T	N/A	InterM

2-7 Cable List / REC mode (Adapter)

From		To		Length (m)	Shielding	
Type	I/O Port	Type	I/O Port		Cable	backshell
EUT	DC IN	Adapter	DC OUT	1.2	NO	Plastic
	LAN	Notebook	LAN	3.0	NO	Plastic
	ALARM IN,GND #1	ALARM #1	-	3.0	NO	Plastic
	ALARM OUT, GND #1	ALARM #2	-	3.0	NO	Plastic
	Micro SD Card	Micro SD Card	-	-	-	-
	AUDIO IN, GND #2	Mobile phone	AUX	3.0	NO	Plastic
	AUDIO OUT, GND #2	Speaker	Speaker IN	3.0	NO	Plastic
Adapter	AC IN	AC Power Source	2 Pin AC Line	-	NO	Plastic

/ REC mode (POE)

From		To		Length (m)	Shielding	
Type	I/O Port	Type	I/O Port		Cable	backshell
EUT	LAN	PoE Injector	LAN #1	3.0	NO	Plastic
	ALARM IN,GND #1	ALARM #1	-	3.0	NO	Plastic
	ALARM OUT, GND #1	ALARM #2	-	3.0	NO	Plastic
	Micro SD Card	Micro SD Card	-	-	-	-
	AUDIO IN, GND #2	Mobile phone	AUX	3.0	NO	Plastic
	AUDIO OUT, GND #2	Speaker	Speaker IN	3.0	NO	Plastic
PoE Injector	LAN #2	Notebook	LAN	3.0	NO	Plastic
	AC IN	AC Power Source	2 Pin AC Line	-	NO	Plastic

3. Test Report

3.1 Summary of tests

Parameter	Applied Standard	Status
I. Emission		
Radiated Emission	EN 55032:2015	C
Conducted Emission	EN 55032:2015	C
Harmonic Current Emission	EN 61000-3-2:2014	NA ^{Note 3}
Voltage Fluctuations and Flicker	EN 61000-3-3:2013	C
II. Immunity		
Electrostatic Discharge	EN 61000-4-2:2009	C
RF Electromagnetic field	EN 61000-4-3:2006/A1:2008/A2:2010	C
Fast Transients Common mode	EN 61000-4-4:2012	C
Surges, line to line and line to ground	EN 61000-4-5:2014/A1:2017	C
RF common mode	EN 61000-4-6:2014/AC:2015	C
Voltage dips and Interruptions	EN 61000-4-11:2004/A1:2017	C
Main supply voltage variations	EN 50130-4:2011/A1:2014	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: We did not test EN61000-3-2 (Harmonic current emissions) for the DC-S6283HRXL because equipment whose rated power is less or equal 75W don't need to be tested.

3.2 EMISSION

3.2.1 Conducted emissions

Definition:

The test assesses the ability of the EUT to limit its internal noise from being present on the AC mains Power In/Output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Measurement Frequency range	: 150 kHz – 30 MHz
Test method	: EN 55032:2015
Measurement RBW	: 9 kHz
Test mode	: REC mode (Adapter), REC mode (POE)
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

A sample calculation:

COR. F (correction factor)= LISN Insertion loss + Cable loss + Pulse Limiter Factors

Emission Level= meter reading + COR.F

Limits for conducted disturbance at the mains ports of class A ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	79 dBuV	66 dBuV
(0.5 – 30) MHz	73 dBuV	60 dBuV

Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Limits for conducted disturbance at the mains ports of class B ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	(66 – 56) dBuV	(56 - 46) dBuV
(0.5 – 5) MHz	56 dBuV	46 dBuV
(5 – 30) MHz	60 dBuV	50 dBuV

Note: The limits will decrease with the frequency logarithmically within 0.15 MHz to 0.5 MHz

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class A equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 – 0.5) MHz	(97 – 87) dBuV	(84 – 74) dBuV	(53 – 43) dBuV	(40 – 30) dBuV
(0.5 – 30) MHz	87 dBuV	74 dBuV	43 dBuV	30 dBuV

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class B equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 – 0.5) MHz	(84 – 74) dBuV	(74 – 64) dBuV	(40 – 30) dBuV	(30 – 20) dBuV
(0.5 – 30) MHz	74 dBuV	64 dBuV	30 dBuV	20 dBuV

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Conducted emissions (LINE) / REC mode (Adapter)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : DC-T4533HRX


Phase : LINE

Test Mode : REC mode (Adapter)

Test Power : 230 / 50

Temp./ Humi. : 25'C / 43% R.H.

Test Engineer : CHO J H



Trace: 1

Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.151	47.87	19.08	19.46	67.33	38.54	79.00	66.00	11.67	27.46
0.169	46.51	16.71	19.47	65.98	36.18	79.00	66.00	13.02	29.82
0.189	44.15	14.46	19.47	63.62	33.93	79.00	66.00	15.38	32.07
0.204	42.69	12.72	19.47	62.16	32.19	79.00	66.00	16.84	33.81
0.235	36.53	7.82	19.48	56.01	27.30	79.00	66.00	22.99	38.70
0.475	32.43	4.84	19.51	51.94	24.35	79.00	66.00	27.06	41.65

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted emissions (NEUTRAL) / REC mode (Adapter)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : DC-T4533HRX


Phase : NEUTRAL

Test Mode : REC mode (Adapter)

Test Power : 230 / 50

Temp./ Humi. : 25'C / 43% R.H.

Test Engineer : CHO J H



Trace: 1

Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.153	47.93	20.82	19.47	67.40	40.29	79.00	66.00	11.60	25.71
0.163	47.31	19.00	19.48	66.79	38.48	79.00	66.00	12.21	27.52
0.179	45.54	17.53	19.48	65.02	37.01	79.00	66.00	13.98	28.99
0.185	44.92	17.59	19.48	64.40	37.07	79.00	66.00	14.60	28.93
0.206	42.29	14.57	19.48	61.77	34.05	79.00	66.00	17.23	31.95
0.227	39.70	13.06	19.48	59.18	32.54	79.00	66.00	19.82	33.46
0.466	32.84	9.08	19.51	52.35	28.59	79.00	66.00	26.65	37.41
0.505	31.74	17.18	19.51	51.25	36.69	73.00	60.00	21.75	23.31
0.592	29.27	5.71	19.52	48.79	25.23	73.00	60.00	24.21	34.77

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted emissions (TEL_100 M) / REC mode (Adapter)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : DC-T4533HRX


Phase : TEL_100M

Test Mode : REC mode (Adapter)

Test Power : 230 / 50

Temp./ Humi. : 25'C / 43% R.H.

Test Engineer : CHO J H



Trace: 1

Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.506	39.79	32.46	19.51	59.30	51.97	87.00	74.00	27.70	22.03
16.229	46.53	42.88	19.76	66.29	62.64	87.00	74.00	20.71	11.36
19.709	47.32	43.72	19.86	67.18	63.58	87.00	74.00	19.82	10.42
20.259	47.18	43.66	19.88	67.06	63.54	87.00	74.00	19.94	10.46
23.128	50.21	46.79	19.97	70.18	66.76	87.00	74.00	16.82	7.24
26.488	46.95	43.28	20.09	67.04	63.37	87.00	74.00	19.96	10.63

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted emissions (TEL_100 M) / REC mode (POE)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : DC-T4533HRX


Phase : TEL_100M

Test Mode : REC mode (POE)

Test Power : 230 / 50

Temp./ Humi. : 25°C / 43% R.H.

Test Engineer : CHO J H



Trace: 1

Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.413	38.91	31.98	19.53	58.44	51.51	88.60	75.60	30.16	24.09
16.229	45.14	42.83	19.76	64.90	62.59	87.00	74.00	22.10	11.41
19.709	46.87	43.77	19.86	66.73	63.63	87.00	74.00	20.27	10.37
23.128	49.39	46.19	19.97	69.36	66.16	87.00	74.00	17.64	7.84
24.350	46.06	42.75	20.02	66.08	62.77	87.00	74.00	20.92	11.23
26.488	47.60	44.11	20.09	67.69	64.20	87.00	74.00	19.31	9.80

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

3.2.2 Radiated Emission

Definition:

The test assesses the ability of ancillary equipment to limit their internal noise from being radiated from the enclosure.

We were performed the test according to LTA procedure LTA-QI-04.

Test method	: EN 55032:2015
Measuring Distance	: 10 m for below 1 GHz / 3 m for above 1 GHz
Measurement Frequency range	: 30 MHz – 6 000 MHz
Measurement RBW	: 120 kHz @ 10 m / 1 MHz @ 3 m
Test mode	: REC mode (Adapter), REC mode (POE)
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

- The highest internal source of an EUT is higher than 108 MHz, the measurement shall be made up to 6 GHz.

(The highest internal source of an EUT : 1.25 GHz)

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Limit of 10 m for below 1 GHz

CLASS A

Frequency Range	Quasi-peak
(30 – 230) MHz	40 dBuV/m
(230 – 1 000) MHz	47 dBuV/m

CLASS B

Frequency Range	Quasi-peak
(30 – 230) MHz	30 dBuV/m
(230 – 1 000) MHz	37 dBuV/m

Limit of 3m for above 1 GHz

CLASS A

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	56	76
(3 000 – 6 000) MHz	60	80
NOTE:	The lower limit applies at the transition frequency.	

CLASS B

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	50	70
(3 000 – 6 000) MHz	54	74
NOTE:	The lower limit applies at the transition frequency.	

Radiated Emission (Below 1 GHz) / V _ REC mode (Adapter)



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (Adapter)

Tested by: CHO J H

Date: 2019-05-16



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
35.58	48.55	-14.95	33.60	40.00	6.40	100	218	vertical
38.85	47.72	-14.55	33.17	40.00	6.83	121	154	vertical
48.31	44.16	-13.86	30.30	40.00	9.70	154	12	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / H _ REC mode (Adapter)



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (Adapter)

Tested by: CHO J H

Date: 2019-05-16



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
48.19	31.86	-13.87	17.99	40.00	22.01	124	247	horizontal
216.24	36.96	-14.51	22.45	40.00	17.55	124	125	horizontal
701.97	28.58	-2.65	25.93	47.00	21.07	100	144	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / V _ REC mode (POE)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (POE)

Tested by: CHO J H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
43.46	46.27	-14.12	32.15	40.00	7.85	100	95	vertical
108.81	48.46	-16.69	31.77	40.00	8.23	100	248	vertical
139.25	44.33	-13.22	31.11	40.00	8.89	100	237	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / H _ REC mode (POE)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (POE)

Tested by: CHO J H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
43.82	33.26	-14.08	19.18	40.00	20.82	100	252	horizontal
108.69	34.20	-16.70	17.50	40.00	22.50	100	346	horizontal
249.34	24.01	-12.93	11.08	47.00	35.92	100	112	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Above 1 GHz) _ REC mode (Adapter)


(Above 1 GHz) / V

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (Adapter)

Tested by: CHO J H




(Above 1 GHz) / H

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (Adapter)

Tested by: CHO J H



Manufacture : IDIS CO., LTD.

Test Date

Temp.: Humidity Distance

Model : DC-T4533HRX

2019-05-16

[°C]

: [%]

(m)

TEST mode : REC mode (Adapter)

Freq.(MHz)	Reading(PK)	Reading(AV)	C.F	Result(PK)	Result(AV)	Limit(PK)	Limit(AV)	Margin(PK)	Margin(AV)	Height	Angle	Polarity
MHz	dBuV	dBuV	dB	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	Hor/Ver
1195.0	48.7	35.7	-6.05	42.65	29.65	76.0	56.0	33.35	26.35	100	320	H
1791.3	44.6	31.6	-1.40	43.20	30.20	76.0	56.0	32.80	25.80	100	212	H
2195.0	45.1	32.1	1.09	46.23	33.23	76.0	56.0	29.77	22.77	100	225	H
1800.0	47.4	34.4	-1.32	46.10	33.10	76.0	56.0	29.90	22.90	100	124	V
1991.9	46.7	33.7	0.35	47.10	34.10	76.0	56.0	28.90	21.90	100	360	V
2197.5	48.3	35.3	1.10	49.40	36.40	76.0	56.0	26.60	19.60	100	348	V

Radiated Emission (Above 1 GHz) _ REC mode (POE)


(Above 1 GHz) / V

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (POE)

Tested by: CHO J H




(Above 1 GHz) / H

EUT/Model No.: DC-T4533HRX

Temp/Humi: 23 / 34

Test Mode : REC mode (POE)

Tested by: CHO J H



Manufacture : IDIS CO., LTD.

Test Date

Temp.: Humidity Distance

Model : DC-T4533HRX

2019-05-16

[°C]

: [%]

(m)

TEST mode : REC mode (POE)

Freq.(MHz)	Reading(PK)	Reading(AV)	C.F	Result(PK)	Result(AV)	Limit(PK)	Limit(AV)	Margin(PK)	Margin(AV)	Height	Angle	Polarity
MHz	dBuV	dBuV	dB	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	Hor/Ver
1801.9	43.2	31.2	-1.31	41.89	29.89	76.0	56.0	34.11	26.11	100	0	H
2000.0	43.7	30.7	0.42	44.09	31.09	76.0	56.0	31.91	24.91	100	231	H
2392.5	43.8	32.8	1.78	45.54	34.54	76.0	56.0	30.46	21.46	100	255	H
1796.9	48.9	35.9	-1.35	47.56	34.56	76.0	56.0	28.44	21.44	100	203	V
1994.4	46.2	33.2	0.36	46.60	33.60	76.0	56.0	29.40	22.40	100	0	V
2393.8	47.5	34.5	1.78	49.27	36.27	76.0	56.0	26.73	19.73	100	48	V

3.2.3 Harmonic Current (AC power input port)

Definition:

This part deals with the Limitation of harmonic currents injected into the public supply system.


We were performed the test according to LTA procedure LTA-QI-04.

Test method	: EN 61000-3-2:2014
Test mode	: REC mode (Adapter)
Rated power	: 3.991 W
Result	: Not Applicable

Measurement Data:

- We did not test EN61000-3-2 (Harmonic current emissions) for the DC-S6283HRXL because equipment whose rated power is less or equal 75W don't need to be tested.

Harmonic Current (AC power input port) / REC mode (Adapter)

17th May 2019 - 16:16:13		Page 1/1	IECSoft v2_5a
		IEC61000-3-2:2014 Fluctuating Harmonics	
Instrument Details			
Instrument Model	PPA5511		
Serial Number	162-04957		
Firmware Version	2.168		
N4L Calibration Date	18th September 2017		
Instrument Version	Standard		
Test Settings			
Class	Class A		
Mode	Measured		
Equipment Under Test			
Brand	IDIS CO., LTD.		
Model	DC-T4533HRX		
Serial	N/A		
Impedance Network ID	N/A		
Test Conditions			
	User Entered	Measured	
Rated Voltage	N/A	230.763V	
Rated Current	N/A	49.889mA	
Rated Frequency	N/A	50.000Hz	
Rated Power	N/A	3.991W	
Additional Test Information			
Measured Power Factor	0.347		
Max Current THD	334.11%		
Max THC	55.757mA		
Max Power	4.032W		
Max F.Current	18.086mA		
Average F.Current	17.334mA		
Minimum Current	100A		
Test Duration	2.5 minutes		
Additional Test Details			
Operator	N/A		
Lab Name	N/A		
Location	N/A		
Notes			
Signature			
Results	Test - N/A. Rated Power < 75W		

Test not applicable

With the exception of lighting equipment section 7 of the IEC61000-3-2:2014 standard declares that no Harmonic current limits are specified for equipment with a rated power of 75W or less.

3.2.4 Voltage Variation and Flicking (AC power input port)

Definition:

This section is concerned with the limitation of voltage fluctuations and flicker impressed on the public low-voltage system.


We were performed the test according to LTA procedure LTA-QI-04.

Test method	:	EN 61000-3-3:2013
Test mode	:	REC mode (Adapter)
Result	:	Complies

Measurement Data:

- Refer to the Next page

Voltage Variation and Flicking (AC power input port) / REC mode (Adapter)

17th May 2019 - 19:11:33		Page 1/2	IECSoft v2_5a
		IEC61000-3-3:2013 Ed.3.0 Flickermeter	
Instrument Details			
Instrument Model	PPA5511		
Serial Number	162-04957		
Firmware Version	2.168		
N4L Calibration Date	18th September 2017		
Instrument Version	Standard		
Test Settings			
Class	Voltage		
Mode	Normal (4%)		
Minimum Current	10A		
PST	10.00 minutes		
PLT	12 PSTs		
Equipment Under Test			
Brand	IDIS CO., LTD.		
Model	DX-T4533HRX		
Serial	N/A		
Impedance Network ID	N/A		
Test Conditions			
	User Entered	Measured	
Rated Voltage	N/A	230.767V	
Rated Current	N/A	N/A	
Rated Frequency	N/A	50.000Hz	
Rated Power	N/A	N/A	
D max	0.0675% (Limit: 4.0%)		
T max	0.0000 s (Limit: 0.5 s)		
DC max	0.0058% (Limit: 3.3%)		
Additional Test Details			
Operator	N/A		
Lab Name	N/A		
Location	N/A		
Notes			
Signature			
Results	Phase1: PASS		

17th May 2019 - 19:11:33			Ph:1 Page 2/2			IECSoft v2_5a		
IEC61000-3-3:2013 Ed.3.0 Flickermeter								
Instrument Details								
Instrument Model		PPA5511						
Instrument Serial		162-04957						
Instrument Firmware		2.168						
Equipment Under Test								
Brand		IDIS CO., LTD.						
Model		DX-T4533HRX						
Serial		N/A						
Flicker Test Results								
PST no.	Status	DC (%)	Dmax (%)	Tmax (s)	PST	PST Lim	PLT	PLT Lim
1	Phase1: PASS	0.006	0.05406	0	0.082	1.00	N/A	N/A
2	Phase1: PASS	0.006	0.06199	0	0.082	1.00	N/A	N/A
3	Phase1: PASS	0.006	0.06199	0	0.082	1.00	N/A	N/A
4	Phase1: PASS	0.006	0.06199	0	0.082	1.00	N/A	N/A
5	Phase1: PASS	0.006	0.06199	0	0.082	1.00	N/A	N/A
6	Phase1: PASS	0.006	0.06199	0	0.082	1.00	N/A	N/A
7	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A
8	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A
9	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A
10	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A
11	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A
12	Phase1: PASS	0.006	0.06747	0	0.082	1.00	N/A	N/A

3.3 IMMUNITY

3.3.1 Electrostatic Discharge

Definition:

The test assesses the ability of the EUT to operate as intended in the event of an electrostatic discharge.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	: 2019.05.23.
Test method	: EN 61000-4-2 :2009
Temperature / Humidity / Pressure	: 24 °C / 38 % R.H. / 100 kPa
Discharge Impedance	: $(330 \pm 10\%) \Omega / (150 \pm 10\%) \text{ pF}$
Type of Discharge (air discharge)	: $\pm 2 \text{ kV}, \pm 4 \text{ kV}, \pm 8 \text{ kV}$
Type of Discharge (contact discharge)	: $\pm 6 \text{ kV}$
Number of discharges at each point	: 10 of each polarity
Discharge Repetition on Rate	: 1 / sec
Test mode	: REC mode (Adapter), REC mode (POE)
Result	: Complies

Measurement Data:

MODE : REC mode (Adapter)

1-1. Indirect Discharge

No.	Position	Kind of Discharge	Results	Remarks
1	HCP	Contact	Complies	No reaction recognized
2	VCP	Contact	Complies	No reaction recognized

1-2. Direct Discharge

No.	Position	Kind of Discharge	Result	Remarks
1	Enclosure	Contact	Complies	No reaction recognized
2	Lens	Air	Complies	No reaction recognized
3	Screw	Contact	Complies	No reaction recognized
4	Micro SD Card	Air	Complies	No reaction recognized
5	ALARM IN, GND #1, GND #2, ALARM OUT, AUDIO IN, AUDIO OUT, LAN, DC IN	Air	Complies	No reaction recognized

MODE : REC mode (POE)

1-2. Indirect Discharge

No.	Position	Kind of Discharge	Results	Remarks
1	HCP	Contact	Complies	No reaction recognized
2	VCP	Contact	Complies	No reaction recognized

1-2. Direct Discharge


No.	Position	Kind of Discharge	Result	Remarks
1	Enclosure	Contact	Complies	No reaction recognized
2	Lens	Air	Complies	No reaction recognized
3	Screw	Contact	Complies	No reaction recognized
4	Micro SD Card	Air	Complies	No reaction recognized
5	ALARM IN, GND #1, GND #2, ALARM OUT, AUDIO IN, AUDIO OUT, LAN	Air	Complies	No reaction recognized

※ Results are complies in each test mode.

ESD TEST POINT

MODE : REC mode (Adapter)



← Air discharge
← Contact discharge



ESD TEST POINT

MODE : REC mode (POE)

← Air discharge
← Contact discharge



3.3.2 RF Electromagnetic Field

Definition:

The test assesses the ability of the EUT to operate as intended in the presence of a radio frequency electromagnetic field disturbance.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.05.26.
Test method	:	EN 61000-4-3:2006/A1:2008/A2:2010
Temperature / Humidity / Pressure	:	23 °C / 36 % R.H. / 100 kPa
Frequency range	:	80 MHz to 2,700 MHz
Test level	:	10 V/m (measured unmodulated)
Amplitude Modulation	:	AM, 80 %, 1 kHz Sinusoidal PM, 1 Hz (0.5s ON : 0.5s OFF)
Step size	:	1 % of fundamental
Dwell Time	:	3 s
Test mode	:	REC mode (Adapter), REC mode (POE)
Result	:	Complies

Measurement Data:

MODE : REC mode (Adapter)

Port	Side	Result	Remarks
Horizontal	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized
Vertical	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized

MODE : REC mode (POE)

Port	Side	Result	Remarks
Horizontal	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized
Vertical	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.3 Electrical fast transients

Definition:

The test assesses the ability of the EUT to operate as intended in the event of fast transients presence on one of the input/output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.05.24.
Test method	:	EN 61000-4-4:2012
Temperature / Humidity / Pressure	:	25 °C / 39 % R.H. / 100 kPa
Cable length	:	> 3 m
Test level	:	2.0 kV (AC power input port) 1.0 kV (Signal port)
Polarity	:	Negative/ positive
Repetition frequency	:	100 kHz
Test mode	:	REC mode (Adapter), REC mode (POE)
Result	:	Complies

Measurement Data:

MODE : REC mode (Adapter)

AC power Line	Test level	Result	Remarks
L – N	± 2 kV	Complies	No reaction recognized

Signal Line	Test level	Result	Remarks
LAN	± 1 kV	Complies	No reaction recognized
AUDIO IN	± 1 kV	Complies	No reaction recognized
AUDIO OUT	± 1 kV	Complies	No reaction recognized
ALARM IN	± 1 kV	Complies	No reaction recognized
ALARM OUT	± 1 kV	Complies	No reaction recognized

MODE : REC mode (POE)

Signal Line	Test level	Result	Remarks
LAN	± 1 kV	Complies	No reaction recognized
AUDIO IN	± 1 kV	Complies	No reaction recognized
AUDIO OUT	± 1 kV	Complies	No reaction recognized
ALARM IN	± 1 kV	Complies	No reaction recognized
ALARM OUT	± 1 kV	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.4 Surge

Definition:

The test assesses the ability of the EUT to operate as intended in the event of surge presence on the AC main power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.05.24.
Test method	:	EN 61000-4-5:2014/A1:2017
Temperature / Humidity / Pressure	:	22 °C / 37 % R.H. / 100 kPa
Test level	:	± 0.5 kV, ±1 kV (line to line) ± 0.5 kV, ± 1 kV, ± 2 kV (line to ground), ± 0.5 kV, ± 1 kV (signal line)
Polarity	:	Negative/ positive
Wave shape	:	1.2/ 50 µs pulse
Number of surges	:	5 (at each phase)
Test mode	:	REC mode (Adapter)
Result	:	Complies

Measurement Data:

MODE : REC mode (Adapter)

Phase	Line	level	Result	Remark
0°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
90°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
180°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
270°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized

Signal Line	level	Result	Remark
LAN	± 0.5, 1.0 kV	Complies	No reaction recognized
AUDIO IN	± 0.5, 1.0 kV	Complies	No reaction recognized
AUDIO OUT	± 0.5, 1.0 kV	Complies	No reaction recognized
ALARM IN	± 0.5, 1.0 kV	Complies	No reaction recognized
ALARM OUT	± 0.5, 1.0 kV	Complies	No reaction recognized

MODE : REC mode (POE)

Signal Line	level	Result	Remark
LAN	$\pm 0.5, 1.0 \text{ kV}$	Complies	No reaction recognized
AUDIO IN	$\pm 0.5, 1.0 \text{ kV}$	Complies	No reaction recognized
AUDIO OUT	$\pm 0.5, 1.0 \text{ kV}$	Complies	No reaction recognized
ALARM IN	$\pm 0.5, 1.0 \text{ kV}$	Complies	No reaction recognized
ALARM OUT	$\pm 0.5, 1.0 \text{ kV}$	Complies	No reaction recognized

3.3.5 Conducted disturbances, induced by radio-frequency fields

Definition:

The test assesses the ability of the EUT to operate as intended in the presence of a radio frequency electromagnetic disturbance on the input/output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.05.23.
Test method	:	EN 61000-4-6:2014/AC:2015
Temperature / Humidity / Pressure	:	23 °C / 35 % R.H. / 100 kPa
Frequency range	:	0.15MHz – 100 MHz
Test level	:	10 Vrms unmodulated
Amplitude Modulation	:	AM, 80 %, 1 kHz Sinusoidal PM, 1 Hz (0.5s ON : 0.5s OFF)
Step size	:	1 % of fundamental.
Test mode	:	REC mode (Adapter), REC mode (POE)
Result	:	Complies

Measurement Data:

MODE : REC mode (Adapter)

Port	Test level (Vrms)	Result	Remarks
Power Line	10	Complies	No reaction recognized

Signal Port	Test level (Vrms)	Result	Remarks
LAN	10	Complies	No reaction recognized
AUDIO IN	10	Complies	No reaction recognized
AUDIO OUT	10	Complies	No reaction recognized
ALARM IN	10	Complies	No reaction recognized
ALARM OUT	10	Complies	No reaction recognized

MODE : REC mode (POE)

Port	Test level (Vrms)	Result	Remarks
LAN	10	Complies	No reaction recognized
AUDIO IN	10	Complies	No reaction recognized
AUDIO OUT	10	Complies	No reaction recognized
ALARM IN	10	Complies	No reaction recognized
ALARM OUT	10	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.6 Mains supply voltage dips, short interruptions

Definition:

The test assesses the ability of the EUT to operate as intended in the event of voltage dips and interruptions present on the AC mains power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date : 2019.05.24.
 Test method : EN 61000-4-11:2004/A1:2017
 Temperature / Humidity / Pressure : 24 °C / 33 % R.H. / 100 kPa
 Ut : 230 Vac
 Test mode : REC mode (Adapter)
 Result : **Complies**

Measurement Data:

MODE : REC mode (Adapter)

Test Level %Ut	Voltage droop and interruptions %Ut	Duration of Reduction (period)	Result	Remarks
80	20	250	Complies	No reaction recognized
70	30	25	Complies	No reaction recognized
40	60	10	Complies	No reaction recognized
0	100	250	Complies	Adapter OFF during the test. After the test, EUT was operated normally about user's control.

3.3.7 Mains supply voltage variations

Definition:

The test assesses the ability of the EUT to operate as intended in the event of voltage variations present on the AC mains power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.05.24.
Test method	:	EN 50130-4:2011/A1:2014
Temperature / Humidity / Pressure	:	24 °C / 33 % R.H. / 100 kPa
Supply Voltage maximum	:	$U_{nom} + 10 \%$
Supply Voltage minimum	:	$U_{nom} - 15 \%$
Ut	:	230 Vac
Test mode	:	REC mode (Adapter)
Result	:	Complies

Measurement Data:

U_{nom} = Nominal mains voltage. Where provision is made to adapt the equipment to suit a number of nominal supply voltages (e.g. by transformer tap changing), the above conditioning severity shall be applied for each nominal voltage, with the equipment suitably adapted. For equipment which is claimed to be suitable for a range of nominal mains voltages (e.g. 220/240 V) without adaptation, $U_{max} = (\text{Maximum } U_{nom}) + 10 \%$, and $U_{min} = (\text{Minimum } U_{nom}) - 15 \%$. In any case the range of U_{nom} must include the European nominal mains voltage of 230 V.

Mains supply voltage variations

MODE : REC mode (Adapter) / 230 V, 50 Hz

Test LevelCondition		Test Level (V)	Result	Remarks
Unom	+10%	253	Complies	No reaction recognized
Unom	-15%	195.5	Complies	No reaction recognized

APPENDIX A

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment are identified by the Test Laboratory.

Conducted emissions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESR	Rohde & Schwarz	101499	2019.07.11	1 year
<input checked="" type="checkbox"/>	Pulse Limiter	ESH3-Z2	Rohde & Schwarz	100710	2020.03.16	1 year
<input checked="" type="checkbox"/>	ISN	ISN T800	TESEQ	27109	2019.09.12	1 year
<input type="checkbox"/>	ISN	ENY81-CA6	Rohde & Schwarz	101565	2019.09.12	1 year
<input type="checkbox"/>	CURRENT PROBE	EZ-17	Rohde & Schwarz	100508	2019.09.06	1 year
<input type="checkbox"/>	LISN	ESH3-Z6	Rohde & Schwarz	100378	2019.09.07	1 year
<input type="checkbox"/>	LISN	ESH3-Z6	Rohde & Schwarz	101468	2019.09.07	1 year
<input checked="" type="checkbox"/>	LISN(main)	ENV216	Rohde & Schwarz	100408	2019.10.10	1 year
<input type="checkbox"/>	LISN(sub)	LT32C/10	AFJ	32031518210	2019.09.06	1 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3_ce 20181212a (V9)	AUDIX	-	-	-

Radiated Emission – Below 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESU	Rohde & Schwarz	100092	2019.09.06	1 year
<input checked="" type="checkbox"/>	Amplifier (25 dB)	8447D	HP	2944A07684	2019.09.06	1 year
<input checked="" type="checkbox"/>	BILOG Antenna	VULB9168	SCHWARZBECK	775	2020.03.16 (KOLAS)	2 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-

Radiated Emission – Above 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESU	Rohde & Schwarz	100092	2019.09.06	1 year
<input checked="" type="checkbox"/>	Amplifier	8449B	HP	3008A00671	2019.09.06	1 year
<input checked="" type="checkbox"/>	HORN ANTENNA	3115	ETS	114105	2019.11.03 (KOLAS)	2 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-

Harmonic Current / Voltage Variation and Flicking

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Precision Power Analyzer	PPA5511	Newtons4th Ltd	162-04957	2019.09.10	1 year
<input checked="" type="checkbox"/>	Reference Impedance Network	ES4152	NF Corp.	9074424	2019.09.07	1 year

Electrostatic Discharge

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	ESD Simulator	ESS-2000	NOISEKEN	8000C03241	2019.09.11	1 year
<input checked="" type="checkbox"/>	ESD GUN	TC-815R	NOISEKEN	ESS0564361	2019.09.11	1 year

RF Electromagnetic Field

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Signal Generator	E4432B	Agilent	MY41310632	2020.03.16	1 year
<input checked="" type="checkbox"/>	Power Meter	E4419B	Agilent	GB38410133	2020.03.16	1 year
<input checked="" type="checkbox"/>	Power Sensor	E9300A	Agilent	MY41497992	2020.03.16	1 year
<input checked="" type="checkbox"/>	Power Sensor	E9300A	Agilent	MY41497618	2020.03.16	1 year
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA0300KL-300	INFINITECH	0300KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA2000KL-120	INFINITECH	200KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA4500KL-70	INFINITECH	4500KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA0750KL-300	INFINITECH	0750KL 1507 001	-	-
<input checked="" type="checkbox"/>	Log.-Per.Antenna (80 MHz ~ 3 GHz)	K9128	RAPA	NONE	-	-
<input type="checkbox"/>	Signal Generator	E4438C	Agilent	MY42080843	2019.09.06	1 year
<input type="checkbox"/>	HORN ANTENNA	3115	ETS	00055005	-	-

Electrical fast transients

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	Compact NX	EMTEST	P1725200196	2019.09.06	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX	EMTEST	P1745207276	2019.09.06	1 year
<input checked="" type="checkbox"/>	Capacitive Coupling Clamp	CCI	EMTEST	P1744207071	2019.09.06	1 year

Surge

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	Compact NX	EMTEST	P1725200196	2019.09.06	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX	EMTEST	P1745207276	2019.09.06	1 year
<input checked="" type="checkbox"/>	CDN	CNV 508T5	EMTEST	P1742204978	2019.09.07	1 year
<input type="checkbox"/>	CDN	CNV 508N1	EMTEST	P1742204940	2019.09.07	1 year

Conducted disturbances, induced by radio-frequency fields

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Signal generator	SML03	R&S	103026/0013	2020.03.16	1 year
<input checked="" type="checkbox"/>	POWER METER	NRVD	R&S	101689	2020.03.16	1 year
<input checked="" type="checkbox"/>	POWER Sensor	URV5-Z2	R&S	100755	2020.03.16	1 year
<input checked="" type="checkbox"/>	POWER Sensor	URV5-Z2	R&S	100756	2020.03.16	1 year
<input checked="" type="checkbox"/>	RF Power Amplifier	FLL75A	FRANKONIA	1033	-	-
<input checked="" type="checkbox"/>	EM INJECTION CLAMP	TSIC-23	F.C.C	529	2020.03.25	1 year
<input type="checkbox"/>	CDN (M1)	TSCDN-M1-16A	F.C.C	07004	2020.03.16	1 year
<input checked="" type="checkbox"/>	CDN (M2)	TSCDN-M2-16A	F.C.C	07008	2019.09.06	1 year
<input type="checkbox"/>	CDN (M2)	TSCDN-M2-16A	F.C.C	07009	2020.03.16	1 year
<input type="checkbox"/>	CDN (M3)	TSCDN-M3-16A	F.C.C	07016	2020.03.16	1 year
<input type="checkbox"/>	CDN (M3)	TSCDN-M3-16A	F.C.C	07017	2019.09.06	1 year

Mains supply voltage dips, short interruptions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	Compact NX	EMTEST	P1725200196	2019.09.06	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX	EMTEST	P1745207276	2019.09.06	1 year

Mains supply voltage variations

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	Compact NX	EMTEST	P1725200196	2019.09.06	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX	EMTEST	P1745207276	2019.09.06	1 year

APPENDIX B

PERFORMANCE CRITERIA

Performance criteria

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test (see Clause 6), after the conditioning.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at 10 V/m, providing.

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable setting etc.)

(b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and

(c) there is no observable deterioration of the picture at 1 V/m.

The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of the bursts is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test

(see Clause 6), after the conditioning.

Slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of the surges is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test

(see Clause 6), after the conditioning.

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators occurs at $U_0 = 130 \text{ dB}\mu\text{V}$.

For components of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at $U_0 = 140 \text{ dB}\mu\text{V}$, providing

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable settings, etc.)

(b) at $U_0 = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used, and

(c) there is no observable deterioration of the picture at $U_0 = 120 \text{ dB}\mu\text{V}$.

The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

Voltage dip/interruption

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

It is permitted to use ancillary equipment (e.g. A UPS) to meet the requirements of this clause. This shall be detailed in the test report and the manufacturer's installation manual.

Signaling a mains fault during the 100 % voltage reduction test is permitted.


Mains supply voltage variations

There shall be no damage, malfunction or change of status due to the different supply voltage conditions. The EUT shall meet the acceptance criteria for the functional test(see Clause 6), during the conditioning.

APPENDIX C

PHOTOGRAPHS

Conducted emission (Maximum emission configuration) / REC mode (Adapter)




Conducted emission (Maximum emission configuration) _ TEL / REC mode (Adapter)




Conducted emission (Maximum emission configuration) _ TEL / REC mode (POE)





Radiated emission (Maximum emission configuration)-Below 1 GHz / REC mode (Adapter)





Radiated emission (Maximum emission configuration)-Below 1 GHz / REC mode (POE)




Radiated emission (Maximum emission configuration) – Above 1GHz / REC mode (Adapter)



Radiated emission (Maximum emission configuration) – Above 1GHz / REC mode (POE)



Harmonic Current / Voltage Variation and Flicking / REC mode (Adapter)




Electrostatic discharge / REC mode (Adapter)




Electrostatic discharge / REC mode (POE)



RF Electromagnetic Field / REC mode (Adapter)



RF Electromagnetic Field / REC mode (POE)



Electrical fast transients / REC mode (Adapter)



Electrical fast transients / REC mode (POE)




Surge / REC mode (Adapter)




Surge / REC mode (POE)



Conducted Disturbances, Induced by Radio-Frequency Fields / REC mode (Adapter)



Conducted Disturbances, Induced by Radio-Frequency Fields / REC mode (POE)



Main supply voltage (dips, variations) short interruptions / REC mode (Adapter)



EUT



EUT

